

Modular Chassis

19" chassis - 4 Slots

Description: 4 slots or 3 + 1 MNG slot, redundant power supply (option)
LED Indicators: Power Supply Main/Secondary, Fan
Dimensions: H: 1.5U 6.7cm (2.7") x W: 48.3cm (19.0") x D: 15.1cm (6.0")
Input Voltage: AC: 90-264VAC, 47-440Hz,
 DC: 36-72 VDC (-48V)

Max Input Power Consumption: 53W
DC Power Output: 8PU
Safety and Emission: CE, FCC, Part 15, EN60950

Environment: Operating: 0 to 45°C (32 to 113°F), Storage: -40 to 85°C (-40 to 185°F), Humidity: 10% to 90% non-condensing



Desktop - 2 Slots

Description: 2 slots or 1 + 1 MNG slot
LED Indicators: Power Supply
Dimensions: H: 1.5U 7.0cm (2.75") x W: 14.0cm (5.5") x D: 21.5cm (8.5")
Input Voltage: AC: 90-264VAC, 47-440Hz,
 DCL: 9-36 VDC
 DCH: 36-72 VDC

Max Input Power Consumption: 16W
DC Power Output: 3PU
Safety and Emission: CE, FCC, Part 15, EN60950

Environment: Operating: 0 to 45°C (32 to 113°F), Storage: -40 to 85°C (-40 to 185°F), Humidity: 10% to 90% non-condensing



Desktop - 1 Slot

Description: 1 slots
LED Indicators: Power Supply
Dimensions: H: 1U 4.4cm (1.75") x W: 14.0cm (5.5") x D: 20cm (7.8")
Input Voltage: AC: 90-264VAC, 47-440Hz,
 DCL: 9-36 VDC
 DCH: 36-72 VDC

Max Input Power Consumption: 16W
DC Power Output: 2PU
Safety and Emission: CE, FCC, Part 15, EN60950

Environment: Operating: 0 to 45°C (32 to 113°F), Storage: -40 to 85°C (-40 to 185°F), Humidity: 10% to 90% non-condensing



Desktop - 1 Slot+

Description: 1 slots (includes internal SNMP management)
LED Indicators: MNG LEDs (Init, Sys, Power Supply Main/Sec, Outband/Inband, Link, Act)
Connectors: RJ-45 10BaseTX, DB9 male Console/RS-232
Dimensions: H: 5.3cm (2.1") x W: 13.5cm (5.3") x D: 21.0cm (8.3")
Input Voltage: AC: 90-264VAC, 47-440Hz,
 DCL: 9-36 VDC
 DCH: 36-72 VDC

Max Input Power Consumption: 16W
DC Power Output: 2PU
Safety and Emission: CE, FCC, Part 15, EN60950

Environment: Operating: 0 to 45°C (32 to 113°F), Storage: -40 to 85°C (-40 to 185°F), Humidity: 10% to 90% non-condensing

